

## Low VOC “E” Stains (18 Series)

To: MSDS User

Please find enclosed the material safety data sheet as per your request. The information presented in these forms is believed to be correct and sufficient to meet the requirements of the OSHA Hazard Communication Standard 29CFR 1910.1200.

These forms should be made available to all those who handle or may otherwise be exposed to the product(s).

The supplied material safety data sheet covers the common hazardous ingredients associated with more than one product. This is supplied in accordance with 29CFR 1910.1200 paragraph (g)(4), and Cal OSHA T8 CCR section 5194 (g)(4) which states: “where complex mixtures have similar hazards and contents ...but the specific composition varies from mixture to mixture ... the manufacturer may prepare one material safety data sheet to apply to all of these similar mixtures.

This MSDS and environmental data sheet is designed to address the safe use and handling of the R.J. McGlennon Company products that are listed below. It is not intended to address specific technical properties of an individual product.

See R.J. McGlennon Co. individual **Product Data Sheets** for VOC and other specific technical data.

This MSDS (identified as 18MSD Low VOC “E” Stains) covers all stain products (both stock and custom) which are labeled as an 18 series stain.

Following is a listing of our stock products that are made in this 18 series.

### Stock Products in 18 Series

SE-710 Lite Oak  
SE-711 Dark Oak  
SE-712 Medium Walnut  
SE-713 Honey Maple  
SE-714 Medium  
SE-715 Golden  
SE-716 Fruitwood  
SE-717 Mahogany  
SE-719 Medium Oak  
SE-720 Lite Oak  
SE-721 Pecan

**PRODUCT NAME:** 18 SERIES STAINS / ALL COLORS  
**PRODUCT CODE:** 18MSD

**HMIS CODES:** H F R P  
2 3 0 H

===== SECTION I - MANUFACTURER IDENTIFICATION =====

**MANUFACTURER'S NAME:** R. J. McGLENNON CO. INC.  
**ADDRESS :** 198 UTAH ST.  
SAN FRANCISCO, CA 94103

**EMERGENCY PHONE :** (800)424-9300                      **DATE REVISED :** 08/25/99  
**INFORMATION PHONE :** (415)552-0311                      **NAME OF PREPARER :** J. Davis  
**DATE PRINTED :** 3/18/2008

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE MM HG @ TEMP	WEIGHT PERCENT
-----			
* XYLENE	1330-20-7	5.1      68 Deg F	52.20
OSHA PEL EXPOSURE LIIMT: 100 ppm TWA			
ACGITH TLV EXPOSURE LIMIT: 100 ppm TWA			
OSHA STEL: 150 ppm			
ACETONE	67-64-1	185.0    68 Deg F	7.0
OSHA PEL EXPOSURE LIMIT: 750 ppm - TWA			
ACGIH TLV EXPOSURE LIMIT: 750 ppm - TWA			
OSHA STEL : 1000 ppm			
LIGHT AROMATIC SOLVENT NAPHTHA	64742-95-6	3.0      68 Deg F	1.0
OSHA PEL EXPOSURE LIMIT: 100 ppm			
ACGIH TLV EXPOSURE LIMIT: 25 ppm			
OTHER EXPOSURE LIMIT: N/A			

\* Indicates this product contains EPCRA section 313 chemical(s) subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).  
This information must be included in all MSDS's that are copied and distributed for this material.    WARNING: This product contains a chemical known to the state of California to cause cancer, birth defects, or other reproductive harm.

WARNING: This product contains flammable solvent(s).

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

**BOILING RANGE:** 133 Deg F - 308 Deg F                      **SPECIFIC GRAVITY (H2O=1):** .92  
**VAPOR DENSITY:** HEAVIER THAN AIR                      **EVAPORATION RATE:** SLOWER THAN ETHER  
**SOLUBILITY IN WATER:** NEGLIGIBLE  
**APPEARANCE AND ODOR:** TRANSLUCENT COLORED LIQUID WITH ORGANIC SOLVENTS ODOR

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

**FLASH POINT:** 15 Deg.F.                                      **METHOD USED:** SETAFLASH  
**FLAMMABLE LIMITS IN AIR BY % OF VOLUME-** LOWER: 1.0%    UPPER: 12.8%

**EXTINGUISHING MEDIA:** FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

**SPECIAL FIREFIGHTING PROCEDURES**

WEAR A SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WITH APPROPRIATE TURN-OUT GEAR AND CHEMICAL RESISTANT PERSONAL PROTECTIVE EQUIPMENT.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY. STATICALLY BOND (GROUND) ALL METAL CONTAINERS DURING LIQUID TRANSFER TO PREVENT STATIC ELECTRICITY DISCHARGE.

=====**SECTION V - REACTIVITY DATA**=====**STABILITY**

STABLE UNDER NORMAL CONDITIONS

**CONDITIONS TO AVOID**

ALL SOURCES OF IGNITION: HEAT, SPARKS, STATIC ELECTRICITY, OPEN FLAMES

**INCOMPATIBILITY (MATERIALS TO AVOID)**

AVOID CONTACT WITH: STRONG OXIDIZING AGENTS

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

CARBON DIOXIDE, CARBON MONOXIDE, HYDROCARBON COMPOUNDS

**HAZARDOUS POLYMERIZATION**

WILL NOT OCCUR

=====**SECTION VI - HEALTH HAZARD DATA**=====**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

INHALATION: EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION. OTHER INHALATION SYMPTONS CAN INCLUDE NAUSEA, DIZZINESS, HEADACHE.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

SKIN: EXPOSURE CAUSES SKIN IRRITATION. PROLONGED OR REPEATED EXPOSURE MAY DRY SKIN. SYMPTOMS MAY INCLUDE REDNESS, BURNING, DRYING, AND CRACKING. EYES: PRIMARY IRRITATION. SYMPTOMS INCLUDE STINGING, TEARING, REDNESS.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

SKIN ABSORPTION IS POSSIBLE, AND MAY BE HARMFUL. BUT HARMFUL EFFECTS ARE NOT EXPECTED FROM INCIDENTAL CONTACT THROUGH NORMAL USE.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

SWALLOWING IS HARMFUL. SYMPTOMS INCLUDE GASTROINTESTINAL IRRITATION (NAUSEA, VOMITING, DIARRHEA).

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

NONE KNOWN ON PRODUCT AS SUPPLIED

HOWEVER, OVER EXPOSURE TO SECTION II COMPONENTS CAN CAUSE DIZZINESS, NAUSEA OR HEADACHE. EXCESSIVE SKIN CONTACT CAN CAUSE DERMATITIS. EYE CONTACT CAN CAUSE IRRITATION.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No**

THIS MATERIAL IS NOT EXPECTED TO BE CARCINOGENIC IN HUMANS BASED ON NEGATIVE EVIDENCE OF CARCINOGENICITY IN LABORATORY ANIMALS. THIS MATERIAL IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA. SEE OTHER WARNINGS IN SECTION II See California warnings in Section II.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

OVER EXPOSURE TO SECTION II COMPONENTS CAN AGGRAVATE PRE-EXISTING DISORDERS OF KIDNEYS, LIVER AND RESPIRATORY SYSTEM.

**EMERGENCY AND FIRST AID PROCEDURES**

IF ON SKIN: FLUSH EXPOSED AREA WITH LARGE AMOUNTS OF WATER. IF ANY IRRITATION DEVELOPS SEEK MEDICAL ATTENTION. REMOVE CONTAMINATED CLOTHING. LAUNDRY CLOTHING BEFORE REUSE. IF IN EYES: FLUSH WITH WATER WHILE HOLDING EYELIDS OPEN. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. FOR INHALATION, REMOVE TO FRESH AIR, AND IF NAUSEA OR DIZZINESS DEVELOPS, SEEK MEDICAL ATTENTION. IF SWALLOWED DO NOT INDUCE VOMITTING (MATERIAL COMPONENTS PRESENT AN ASPIRATION HAZARD) PLACE PERSON ON LEFT SIDE AND SEEK MEDICAL ATTENTION.

=====**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**=====**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

SMALL SPILL: ABSORB LIQUID ON VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL. LARGE SPILL: ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES, INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS), PREVENT SPREAD OF MATERIAL.

**WASTE DISPOSAL METHOD**

HAZARDOUS WASTE REGULATIONS ARE NOT CONSISTENT THROUGHOUT THE COUNTRY (SOME WASTES ARE NOT HAZARDOUS WASTE UNDER FEDERAL RULES, BUT THE SAME WASTE MAY BE DEFINED AS HAZARDOUS WASTE UNDER STATE RULES).

ANY SPILLS SHOULD BE SOAKED UP WITH INERT ABSORBANT AND COLLECTED IN CONTAINERS. PAINT BOOTH FILTERS MAY BE CONSIDERED HAZARDOUS.

CONTACT YOUR LOCAL HAZARDOUS WASTE AGENCY (WITH INFORMATION FROM THIS MSDS) FOR PROPER DISPOSAL INSTRUCTIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

DO NOT STORE ABOVE 120 DEG.F. DO NOT STORE OR USE NEAR HEAT, SPARKS, OPEN FLAMES, OR ANY SOURCE OF IGNITION.

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS EVEN WHEN EMPTIED-SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPORS, LIQUID, AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

**OTHER PRECAUTIONS**

AVOID SKIN AND EYE CONTACT. DO NOT BREATHE VAPORS. DO NOT TAKE INTERNALLY. USE ONLY WITH ADEQUATE VENTILATION. RAGS SOAKED WITH THIS MATERIAL SHOULD BE SOAKED WITH WATER AND STORED IN A CLOSED CONTAINER SO AS TO PREVENT DEVELOPMENT OF HEAT OR FIRE FROM BUNCHED RAGS. ALL PERSONS WHO USE THIS MATERIAL SHOULD READ AND UNDERSTAND ALL MANUFACTURERS' INSTRUCTIONS AND PRECAUTIONS PRIOR TO USE. THIS MATERIAL IS INTENDED FOR USE IN AN INDUSTRIAL ENVIRONMENT BY TRAINED PERSONNEL ONLY.

=====**SECTION VIII - CONTROL MEASURES**=====

**RESPIRATORY PROTECTION**

IF WORKPLACE EXPOSURE LIMITS(S) OF PRODUCT OR ANY COMPONENT IS EXCEEDED (SEE SECTION II), A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS (CHEMICAL TYPE WITH ORGANIC VAPOR CARTRIDGE) - CONSULT YOUR INDUSTRIAL HYGIENIST.

**VENTILATION**

PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN ALL SECTION II COMPONENTS BELOW THEIR EXPOSURE LIMITS.

**PROTECTIVE GLOVES**

WEAR RESISTANT GLOVES (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER).

**EYE PROTECTION**

CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

EYE BATH AND SAFETY SHOWER. TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING, GLOVES, AND BOOTS.

**WORK/HYGIENIC PRACTICES**

WASH HANDS PRIOR TO EATING. DO NOT SMOKE NEAR THIS PRODUCT.

=====**SECTION IX - DISCLAIMER**=====

THE INFORMATION IN THIS MSDS AND ENVIRONMENTAL DATA SHEET WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS ACCURACY OR COMPLETENESS. RECIPIENTS ARE ADVISED TO CONFIRM THE CURRENT ACCURACY IN ADVANCE OF NEEDS.