



LOW VOC MAR RESISTANT LACQUER

R.J. McGlennon Co. Inc.
198 Utah Street
San Francisco, CA 94103

Product Data Sheet

Phone (415) 552-0311
Fax (415) 552-8055

28 SERIES S-159 LOW VOC MAR RESISTANT SANDING SEALER

Description S-159 is a fast drying, low VOC mar resistant lacquer sanding sealer. It is designed as a companion product for our 28 series Low VOC Mar Resistant lacquers. This compliance sanding sealer has exceptional build and toughness. It is recommended for use on all interior wood surfaces.

Specifications Weight per Gallon: 7.31 Coating VOC: 550 G/L 4.58 Lb/gal
Solids by Weight %: 22.00 Material VOC: 245 G/L 2.04 Lb/gal
Solids by Volume %: 15.97 VOC Weight Ratio = 1.27 LbVOC/Lb Solid
Coverage @ 1mil 257 SqFt./Gal.
Viscosity: 18 - 25 Seconds Zahn 2



Surface Preparation Apply over properly prepared wood surfaces. Surfaces must be clean and free of dirt, grease and water. Remove any wax or old finish.

Mixing & Thinning Product as supplied is ready to spray. No further thinning is required or recommended. However, if any reduction is desired, then we recommend thinning with Acetone, as this will not change the VOC content. Additional thinning with a non-exempt thinner will raise the VOC content. Thoroughly mix the material by stirring or shaking prior to application.

Application & Dry S-159 sanding sealer is designed for spray application only. It may be applied with conventional, airless, air-assist airless or HVLP spray equipment. S-159 will dry to sand within 20 minutes under standard conditions, (when applied to approximately 1 mil dry film thickness).
R.J. McGlennon Co. recommends 1 coat of sanding sealer (maximum 1 mil dry film), with any additional film build completed by the topcoat.
The total film build should be 2-4 mils dry film. Do not exceed 5 mils dry film.

Performance & Durability The 28 Series Mar Resistant Lacquers are tough and durable, and are recommended for applications requiring surface mar resistance. This series of lacquers is for interior use only.
Forms an easy sanding sealer coat for wood. Designed to be used as part of a mar resistant lacquer system.

Environmental & Safe Handling Maximum Coating VOC content as supplied is 550 G/L (4.58 Lbs/Gal.)
Warning: flammable mixture. Do not use near heat, sparks, flames, or any ignition sources. Do not cut empty containers. Use only with adequate ventilation. Dispose of any product only in accordance with all applicable regulations. See product material safety data sheet titled "29MSD Maclac Low VOC W/W Lacquers" for full details.

LIMITED WARRANTY

The information contained herein is offered to assist customers in determining whether our products are suitable for their applications. We request that customers examine our products before use and satisfy themselves as to their suitability. We warrant that our products will meet our written specifications. Since application circumstances, substrate condition and product intermix are beyond our control, we cannot guarantee results under all possible situations. R.J. McGlennon Co. Inc. makes no representation as to the results the user will achieve.
Technical advice furnished by seller or any seller's agents shall not constitute a warranty. Any liability arising out of any condition resulting from the use of any R.J. McGlennon Co. Inc. product shall be limited to replacement of such product.